



(19)

(11) Publication number: 0:

Generated Document.

# PATENT ABSTRACTS OF JAPAN

(21) Application number: 03319283

(51) Intl. Cl.: G01M 3/26 B01D 65/10 G01

(22) Application date: 03.12.91

(30) Priority: (43) Date of application publication: 25.06.93 (84) Designated contracting states:	(71) Applicant: ASAHI CHEM IND CO (72) Inventor: FUJINO KAZUHITO ANAMI YASUYUKI (74) Representative:
---	---

## (54) LEAKAGE INSPECTION METHOD OF FILM- SEPARATION DEVICE

(57) Abstract:

**PURPOSE:** To enable presence or absence of leakage defect of a film to be detected readily by filling a pressurized gas into one chamber which is isolated by a film, enclosing a liquid or a gas into the other chamber and at the same time providing a pressure-detection means, and then measuring pressure of a chamber at a side where gas leaks.

**CONSTITUTION:** A stock solution inside a bundle 4 of a hollow yarn filtering film and upper and lower stock solution chambers 2 is delivered out of a system. Then, a valve 11 is closed and valves 13 and 14 are shielded while liquid is filled into a filtering liquid chamber 3. After that, a pressurized air is filled into a stock solution chamber 2 and the hollow yarn 4. On the other hand, a filtering liquid chamber 3 is in the

BEST AVAILABLE COPY

same pressure as the pressurized air in liquid-sealing state. At this time, an air chamber 5 is shielded by a valve 12 and a normal-pressure air is filled inside. Then, the valve 12 is opened and a pressure of the liquid-filtering chamber 3 is reduced to a pressure which is lower than the pressurized air. At this time, when the filtering film is in a wet state, permeation of gas within a porous film is prevented extremely by surface tension, pressure increase at a liquid side of a sound film without any defect is slight, and the increase speed is calibrated previously. A pressure within the filtering liquid chamber 3 increases abnormally when there are defects.

COPYRIGHT: (C)1993,JPO&Japio

